

COMBiLiFT

LIFTING INNOVATION

Coolant System Protective Agents Approval List

Combilift trucks manufactured after 02/2018 left the factory with a mixture of 50% water to 50% Glystantin® G64® coolant concentrate in the engines cooling system.

Coolants from the following table are approved for use by Combilift.

Manufacturer	Brand	Marketing Area	Remarks
DEUTZ AG	DEUTZ Kühlsystemsenschutzmittel DQC-CA	weltweit / worldwide	
AGCO	FENDT Kühlerfrostschutz GRÜN 48 EXTRA	weltweit / worldwide	
ARAL	ARAL Antifreeze Extra	Europa / Europe	
Arteco	Havoline AFC	Europa, Asien / Europe, Asia	
AVIA AG	AVIA ANTIFREEZE APN	Deutschland, Österreich / Germany, Austria	
AVIAFLUID International LLC	MAXCool Hybrid	weltweit / worldwide	
BASF SE	Glystantin® G48® blue-green	weltweit / worldwide	
BayWa AG	TECTROL COOLPROTECT	Europa / Europe	
Bucher AG Langenthal	MOTOREX COOLANT G48® Concentrate MO-TOREX COOLANT G48 Ready to use	weltweit / worldwide weltweit / world-wide	
COPARTS Autoteile GmbH	CAR1 Premium-Longlife Kühlerschutz C48	weltweit / worldwide	Ready-Mix
Castrol Limited	Castrol Radicool NF	weltweit / worldwide	
CEPSA	XTAR SUPER COOLANT HYBRID NF 50%	weltweit / worldwide	Ready-Mix
CLASSIC Schmierstoff GmbH	CLASSIC KOLDA UE G48®	weltweit / worldwide	
Finke Mineralölwerk GmbH	Aviaticon Finkofreeze F48 Aviaticon Finkofreeze F48 RM 50:50	weltweit / worldwide weltweit / world-wide	Ready-Mix

It is advised not to mix different coolant products.

Drain and flush the cooling system before adding any product from the above list *.

* If the truck was produced after 02/2018 and the cooling system still contains Glystantin G64® then it can be safely topped up with Glystantin G64® coolant concentrate mixed to a 50:50 ratio with clean clear **water**.